# NSN 5950-00-905-8835

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-905-8835

#### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.312 inches single mounting facility single center group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

5.062 inches

#### **Body Width:**

4.312 inches

#### **Body Height:**

5.500 inches

#### **Maximum Operating Temp:**

105.0 degrees celsius

# Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

# Thread Size:

0.250 inches single group

#### **Winding Operating Current:**

250.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

1.60 ac kilovolts single component single secondary

#### **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

### Shelf Life:

N/a

# NSN 5950-00-905-8835

Power Transformer - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A058b0