## NSN 5950-00-907-2364

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-907-2364

| Reliability Indicator:  |
|---|
| Not established   |
|   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.688 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure and core single component           |
| Body Length:  |
| 4.688 inches  |
| Body Width:   |
| 4.000 inches  |
| Body Height:  |
| 4.000 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 5 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 20 single group   |
| Thread Size:  |
| 0.044 inches single group   |
| Thread Series Designator:   |
|   |
| Terminal Type And Quantity:   |
| 12 tab, solder lug and 3 solder stud                                      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |