

View Online at <https://aerobasegroup.com/nsn/5950-00-907-8302>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.218 inches single mounting facility single center group

Frequency Rating:

360.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.625 inches

Body Width:

1.375 inches

Body Height:

1.375 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0