

View Online at <https://aerobasegroup.com/nsn/5950-00-909-7763>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.300 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.900 inches

Body Width:

1.600 inches

Body Height:

1.800 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

7.0 milliamperes dc single component single secondary and 11.0 milliamperes dc single component single secondary

Winding Operating Voltage:

300.00 ac volts single component single secondary and 1.00 ac kilovolts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0