## NSN 5950-00-909-7771

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-909-7771

| Reliability Indicator:  |
|---|
| Not established   |
| Overall Length:   |
| 5.160 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 4.580 inches single mounting facility single center group and 4.620 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.480 inches single mounting facility single center group and 3.520 inches single mounting facility single center group |
| Mounting Hole Diameter:   |
| 0.220 inches single group   |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Internal shield brought out to terminal single component  |
| Body Width:   |
| 5.060 inches  |
| Body Height:  |
| 4.900 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Winding Operating Current:  |
| 4.9 amperes ac single component single secondary  |
| Winding Power Rating:   |
| 563.5 volts-amperes single component single secondary   |
| Winding Operating Voltage:  |
| 82.50 ac volts single component single primary  |
| Terminal Type And Quantity:   |
| 7 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-909-7771

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0