

View Online at <https://aerobasegroup.com/nsn/5950-00-911-7015>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.437 inches single mounting facility single center group

Inductance Type:

Swinging

Inductance Rating:

8.20 millihenries single component 1st winding and 80.00 millihenries single component 1st winding

Body Length:

3.375 inches

Body Width:

3.937 inches

Body Height:

5.250 inches

Winding Quantity:

2 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component all winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

4.8 amperes dc single component 1st winding and 8.0 amperes dc single component 1st winding

Dc Resistance Rating In Ohms:

0.150 single component 1st winding

Criticality Code Justification:

Feat

Special Features:

Ref number differnetiating material will be iaw naval inventory control point hx quality control, manufacturing and testing specification available at the dla icp

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0