

View Online at <https://aerobasegroup.com/nsn/5950-00-912-4381>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to six phase single component and three phase to two phase single component

Transformer Winding Connection Type:

Wye-open delta and wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.630 inches

Body Width:

2.500 inches

Body Height:

1.750 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

440.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

54.1 volts-amperes single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary and 26.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

25 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0