

View Online at <https://aerobasegroup.com/nsn/5950-00-912-4381>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component and three phase to six phase single component and three phase to two phase single component

**Transformer Winding Connection Type:**

Wye-open delta and wye-wye

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

3.630 inches

**Body Width:**

2.500 inches

**Body Height:**

1.750 inches

**Maximum Operating Temp:**

170.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 4 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

440.0 milliamperes ac single component 3rd secondary

**Winding Power Rating:**

54.1 volts-amperes single component 4th secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary and 26.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

25 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0