## NSN 5950-00-913-1967

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-913-1967

| Reliability Indicator:   |
|--|
| Not established  |
| Inductance Rating:   |
| 0.33 microhenries single component single winding  |
| Coil Form Type:  |
| Solid single component   |
| Core Construction:   |
| S0lid single component   |
| Body Length:   |
| 0.430 inches   |
| Body Outside Diameter:   |
| Between 0.147 inches and 0.167 inches  |
| Maximum Operating Temp:  |
| 125.0 degrees celsius  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Terminal single group  |
| Rating Method:   |
| Electrical single component single winding   |
| Features Provided:   |
| Tinned wire leads  |
| Winding Operating Current:   |
| 1.3 amperes dc single component single winding   |
| Dc Resistance Rating In Ohms:  |
| 0.130 single component single winding  |
| Quality Factor:  |
| 46 single component single winding   |
| Special Features:  |
| Electro-magnetic shield  |
| Test Data Document:  |
| 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Specification Data:  |
| 96906-ms90537 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |

Yes - demil/mli

Demilitarization:

## NSN 5950-00-913-1967

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0