

View Online at <https://aerobasegroup.com/nsn/5950-00-913-5393>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.187 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.562 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.562 inches

Body Width:

5.156 inches

Body Height:

6.000 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 12 secondary single component

Winding Operating Current:

300.0 milliamperes ac single component 4th secondary

Winding Power Rating:

45.36 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

1 primary winding; 12 secondary windings

Terminal Type And Quantity:

34 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0