

View Online at <https://aerobasegroup.com/nsn/5950-00-913-5536>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.900 inches single mounting facility single center group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.500 inches

Body Width:

2.490 inches

Body Height:

2.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Voltage:

2.80 ac volts single component 1st secondary and 15.30 ac volts single component 1st secondary and 28.80 ac volts single component 1st secondary and 42.30 ac volts single component 1st secondary and 54.80 ac volts single component 1st secondary and 57.60 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0