

View Online at <https://aerobasegroup.com/nsn/5950-00-913-6176>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.312 inches

Body Width:

2.000 inches

Body Height:

1.938 inches

Distance Between Mounting Facility Centers:

2.812 inches single mounting facility single center group

End Application:

Wsd: support equipment, b-52 aircraft; consolidated space operations center; trident hull structure; submarine auxillary and miscellaneous systems; missile, minuteman lgm-30; whidbey island lsd; yellowstone ad-41; forrestal cv; nimitz cvn

Inclosure Type:

Partially enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

26.8 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

117.00 ac volts single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0