

View Online at <https://aerobasegroup.com/nsn/5950-00-914-2805>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

240.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.500 inches

Body Width:

4.500 inches

Body Height:

6.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

7.0 amperes ac single component single secondary and 18.0 amperes ac single component single secondary

Winding Operating Voltage:

48.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0