## NSN 5950-00-915-1199

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-915-1199

| Reliability Indicator:  |
|---|
| Not established   |
| Frequency Rating:   |
| 400.0 hertz single component                                  |
| Input-output Phase Relationship:                              |
| Single phase to single phase single component                 |
| Winding Shielding Method:                                     |
| Internal shield grounded to inclosure single component        |
| Body Length:  |
| 1.750 inches  |
| Body Width:   |
| 1.312 inches  |
| Body Height:  |
| 1.312 inches  |
| Distance Between Mounting Facility Centers:                   |
| 0.890 inches single mounting facility single center group     |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:                                   |
| 2 single group  |
| Mounting Method:  |
| Threaded stud single group                                    |
| Winding Function And Quantity:                                |
| 1 primary single component and 2 secondary single component   |
| Thready Qty Per Inch (tpi):                                   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group                                     |
| Winding Operating Current:                                    |
| 250.0 milliamperes ac single component 3rd secondary          |
| Winding Operating Voltage:                                    |
| 115.00 ac pounds per hour wet single component single primary |
| Special Features:   |
| Case metal material   |
| Thread Series Designator:                                     |
| Unc single group  |
| Terminal Type And Quantity:                                   |
| 6 solder stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-915-1199

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0