NSN 5950-00-915-1496

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5050-00-015-1406

| View Online at https://aerobasegroup.com/nsn/5950-00-915-1496 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.812 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.218 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 2.000 inches |
| Body Height: |
| 2.750 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 800.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 22.60 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0