## NSN 5950-00-915-3535

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-915-3535

| Deliability Indicators                               |
|--|
| Reliability Indicator:  Not established              |
|  |
| Inductance Type:                                     |
| Fixed  |
| Inductance Rating:                                   |
| 30.00 millihenries single component single winding   |
| Frequency Rating:                                    |
| 3.0 kilohertz single component                       |
| Body Length:   |
| 0.688 inches   |
| Body Width:  |
| 0.375 inches   |
| Body Height:   |
| 0.738 inches   |
| Winding Quantity:                                    |
| 1 single component                                   |
| Inclosure Type:                                      |
| Fully enclosed                                       |
| Mounting Facility Quantity:                          |
| 1 single group                                       |
| Mounting Method:                                     |
| Core single group and threaded hole single group     |
| Rating Method:                                       |
| Electrical single component single winding           |
| Thready Qty Per Inch (tpi):                          |
| 48 single group                                      |
| Thread Size:   |
| 0.099 inches single group                            |
| Winding Operating Current:                           |
| 32.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms:                        |
| 14.300 single component single winding               |
| Thread Series Designator:                            |
| Unc single group                                     |
| Terminal Type And Quantity:                          |
| 2 tab, solder lug                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |

No

## NSN 5950-00-915-3535

Reactor - Page 2 of 2



Fiig:

A058b0