NSN 5950-00-918-4430

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-918-4430

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.440 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.120 inches single mounting facility single center group |
| Frequency Rating: |
| 45.0 hertz single component and 5.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 8.000 inches |
| Body Width: |
| 5.500 inches |
| Body Height: |
| 6.620 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 24 single group |
| Thread Size: |
| 0.375 inches single group |
| Winding Operating Current: |
| 350.0 milliamperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 75.00 ac volts single component 1st secondary and 130.00 ac volts single component 1st secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 2 wire lead and 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-918-4430

Power Transformer - Page 2 of 2



Fiig:

A058b0