

View Online at <https://aerobasegroup.com/nsn/5950-00-919-1887>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Impedance Rating In Ohms:

12.5 single component all primary

Frequency Rating:

300.0 hertz single component and 3.5 kilohertz single component

Maximum Transformer Power Rating:

20.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1 to 3-7/16 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.250 inches

Body Width:

1.500 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

60.0 milliamperes ac single component all primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0