

View Online at <https://aerobasegroup.com/nsn/5950-00-919-4545>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches 2nd mounting facili type 2nd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches 2nd mounting facili type 2nd center group

Mounting Slot Width:

0.281 inches 2nd group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internally shielded grounded to core and mounting single component

Body Length:

7.500 inches

Body Width:

0.400 inches

Body Height:

5.875 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 2nd group

Mounting Method:

Bracket 2nd group and slot 2nd group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

12.8 amperes ac single component single secondary

Winding Operating Voltage:

225.00 ac volts single component single primary

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0