

View Online at <https://aerobasegroup.com/nsn/5950-00-919-4546>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.250 inches single mounting facility all center groupings

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility all center groupings

**Mounting Slot Width:**

0.406 inches all groupings

**Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Wye-wye

**Maximum Transformer Power Rating:**

787.2 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

8.750 inches

**Body Width:**

6.000 inches

**Body Height:**

8.500 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 all groupings

**Mounting Method:**

Slot all groupings

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

26.0 amperes ac single component single secondary

**Winding Power Rating:**

787.2 volts-amperes single component single secondary

**Winding Operating Voltage:**

17.50 ac volts single component single secondary

**Special Features:**

Primary neutral tap comprised of terminals 2, 4, 6 and secondary neutral tap comprised of terminals 8, 10

**Terminal Type And Quantity:**

2 terminal block w/screws

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0