# NSN 5950-00-919-4546

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-919-4546

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

6.250 inches single mounting facility all center groupings

## Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility all center groupings

#### Mounting Slot Width:

0.406 inches all groupings

#### **Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

## Input-output Phase Relationship:

Three phase to three phase single component

## **Transformer Winding Connection Type:**

Wye-wye

#### **Maximum Transformer Power Rating:**

787.2 volt-ampere single component

#### Winding Shielding Method:

Internal shield grounded to inclosure and core single component

#### Body Length:

8.750 inches

## Body Width:

6.000 inches

#### Body Height:

8.500 inches

## Maximum Operating Temp:

130.0 degrees celsius

#### Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 all groupings

#### **Mounting Method:**

Slot all groupings

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Winding Operating Current:

26.0 amperes ac single component single secondary

## Winding Power Rating:

787.2 volts-amperes single component single secondary

#### Winding Operating Voltage:

17.50 ac volts single component single secondary

# **Special Features:**

Primary neutral tap comprised of terminals 2, 4, 6 and secondary neutral tap comprised of terminals 8, 10

# NSN 5950-00-919-4546

Power Transformer - Page 2 of 2



## Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0