NSN 5950-00-919-7121

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-919-7121

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.000 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 6.500 inches |
| Body Width: |
| 5.250 inches |
| Body Height: |
| 2.870 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 28 single group |
| Thread Size: |
| 0.250 inches single group |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 6 threaded stud and 7 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |