NSN 5950-00-920-4769

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-920-4769

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.260 inches single mounting facility single center group and 0.270 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.260 inches single mounting facility single center group and 0.270 inches single mounting facility single center group

Mounting Hole Diameter:

0.135 inches single group and 0.145 inches single group

Inductance Type:

Fixed

Inductance Rating:

0.01 henry single component single winding

Frequency Rating:

400.0 hertz single component

Body Length:

Between 0.890 inches and 0.922 inches

Body Width:

Between 0.890 inches and 0.922 inches

Body Height:

0.875 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

0.4 amperes dc single component single winding

Dc Resistance Rating In Ohms:

10.000 single component single winding

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-920-4769

Reactor - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A058b0