## NSN 5950-00-920-4769

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-920-4769

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.260 inches single mounting facility single center group and 0.270 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.260 inches single mounting facility single center group and 0.270 inches single mounting facility single center group

#### Mounting Hole Diameter:

0.135 inches single group and 0.145 inches single group

#### Inductance Type:

Fixed

#### Inductance Rating:

0.01 henry single component single winding

#### **Frequency Rating:**

400.0 hertz single component

#### **Body Length:**

Between 0.890 inches and 0.922 inches

#### **Body Width:**

Between 0.890 inches and 0.922 inches

#### **Body Height:**

0.875 inches

## Maximum Operating Temp:

105.0 degrees celsius

#### Winding Quantity:

1 single component

## Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Unthreaded hole single group

#### **Rating Method:**

Electrical single component single winding

#### Winding Operating Current:

0.4 amperes dc single component single winding

#### Dc Resistance Rating In Ohms:

10.000 single component single winding

#### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5950-00-920-4769

Reactor - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A058b0

