

View Online at <https://aerobasegroup.com/nsn/5950-00-921-3418>

Reliability Indicator:

Not established

Overall Length:

Between 0.375 inches and 0.415 inches

Inductance Rating:

100.00 microhenries single component single winding

Coil Form Type:

Solid single component

Core Construction:

Solid single component

Body Outside Diameter:

Between 0.147 inches and 0.167 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads

Winding Operating Current:

325.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

3.120 single component single winding

Quality Factor:

50 single component single winding

Special Features:

Electro-magnetic shield

Test Data Document:

81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire lead

Specification Data:

96906-ms90537 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0