NSN 5950-00-922-7254

Reactor - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-922-7254

3.000 inches single mounting facility single center group

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

Inductance Type:
Fixed
Inductance Rating:
500.00 microhenries single component single winding
Body Length:
4.375 inches
Body Width:
4.000 inches
Body Height:
4.000 inches
Maximum Operating Temp:
105.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Marintina Mathadi
Mounting Method:
Threaded hole single group
Threaded hole single group
Threaded hole single group Rating Method:
Threaded hole single group Rating Method: Electrical single component single winding
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size:
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current:
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding Dc Resistance Rating In Ohms:
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.010 single component single winding
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.010 single component single winding Thread Series Designator:
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.010 single component single winding Thread Series Designator: Unf single group
Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Operating Current: 35.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.010 single component single winding Thread Series Designator: Unf single group Terminal Type And Quantity:

NSN 5950-00-922-7254

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0