

View Online at <https://aerobasegroup.com/nsn/5950-00-922-9151>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.875 inches single mounting facility single center group

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

7.875 inches

Body Width:

4.500 inches

Body Height:

5.313 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.7 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

1 wire lead and 1 cable w/connector and 1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0