

View Online at <https://aerobasegroup.com/nsn/5950-00-927-0802>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.718 inches

Body Width:

0.593 inches

Body Height:

1.375 inches

Distance Between Mounting Facility Centers:

2.000 inches single mounting facility single center group

End Application:

General purpose electronic test equipment gpete, mine countermeasures support (mcs) class (lph-12), spruance class dd (963), oliver perry class ffg, tarawa class lha, Forrestal class cv, wasp class lhd, Emory S. Land class as, Ticonderoga class cg (47) Nimitz class cvn

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

60.0 milliamperes dc single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

50.00 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0