

View Online at <https://aerobasegroup.com/nsn/5950-00-928-0073>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.750 inches

Body Width:

2.250 inches

Body Height:

3.030 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

300.0 milliamperes ac single component single secondary

Winding Operating Voltage:

26.00 ac volts single component 1st secondary and 37.00 ac volts single component 1st secondary and 59.00 ac volts single component 1st secondary and 70.00 ac volts single component 1st secondary and 96.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0