## NSN 5950-00-928-0073

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-928-0073
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.120 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 450.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
2.750 inches
Body Width:
2.250 inches
Body Height:
3.030 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
300.0 milliamperes ac single component single secondary
Winding Operating Voltage:
26.00 ac volts single component 1st secondary and 37.00 ac volts single component 1st secondary and 59.00 ac volts single component
1st secondary and 70.00 ac volts single component 1st secondary and 96.00 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
9 solder stud
Shelf Life:
N/a

\_\_

**Unit Of Measure:** 

## NSN 5950-00-928-0073

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0