NSN 5950-00-928-7789

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-928-7789 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Wye-wye |
| Body Length: |
| 2.375 inches |
| Body Width: |
| 1.562 inches |
| Body Height: |
| 2.125 inches |
| Inclosure Type: |
| Hermetically sealed with oil |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 160.0 milliamperes dc single component single secondary |
| Winding Operating Voltage: |
| 33.00 ac volts single component single primary and 55.00 ac volts single component single primary and 115.00 ac volts single component |
| single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 14 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-928-7789

Power Transformer - Page 2 of 2



Fiig:

A058b0