

View Online at <https://aerobasegroup.com/nsn/5950-00-929-4910>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.438 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

3.938 inches

**Body Width:**

3.375 inches

**Body Height:**

5.250 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

900.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single secondary

**Test Data Document:**

06053-s0030-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0