NSN 5950-00-930-3176

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-930-3176

D	ام	ia	h	ii	i٤٠	, 1	ın	ч	i	са	4	_	r	
к	еı	ıα	D	Ш	IU	7 I	Ш	u	ı	Ca	ш	υ	Г	

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.873 inches single mounting facility single center group and 0.894 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.873 inches single mounting facility single center group and 0.894 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.250 inches and 1.310 inches

Body Width:

Between 1.250 inches and 1.310 inches

Body Height:

Between 1.620 inches and 1.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Voltage:

9.00 ac volts single component single primary and 26.00 ac volts single component single primary and 115.00 ac volts single component single primary

Test Data Document:

70210-902053 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire hook

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A058b0