NSN 5950-00-931-6235

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-931-6235

| View Online at https://aerobasegroup.com/nsn/5950-00-931-6235 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| External inclosure single component |
| Body Length: |
| 2.812 inches |
| Body Width: |
| 2.370 inches |
| Body Height: |
| 2.750 inches |
| Maximum Operating Temp: |
| 170.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed with oil |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 3 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Voltage: |
| 115.00 ac volts single component all primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 11 wire hook |
| Shelf Life: |
| N/o |

--

Unit Of Measure:

NSN 5950-00-931-6235

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0