NSN 5950-00-932-2676

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-932-2676

| view Online at https://aerobasegroup.com/nsn/5950-00-932-2076 | |
|--|--|
| Reliability Indicator: | |
| Not established | |
| Inductance Rating: | |
| 5.60 millihenries single component single winding | |
| Coil Form Type: | |
| Solid single component | |
| Core Construction: | |
| S0lid single component | |
| Body Length: | |
| Between 0.375 inches and 0.415 inches | |
| Body Outside Diameter: | |
| Between 0.147 inches and 0.167 inches | |
| Aximum Operating Temp: | |
| 25.0 degrees celsius | |
| nclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| erminal single group | |
| Rating Method: | |
| Electrical single component single winding | |
| Features Provided: | |
| ïnned wire leads | |
| Vinding Operating Current: | |
| 6.0 milliamperes dc single component single winding | |
| Dc Resistance Rating In Ohms: | |
| 8.900 single component single winding | |
| Quality Factor: | |
| 15 single component single winding | |
| Special Features: | |
| Electro-magnetic shield | |
| Fest Data Document: | |
| 31349-mil-c-15305 specification (includes engineering type bulletins | , brochures, etc., that reflect specification type data in specification |
| ormat; excludes commercial catalogs, industry directories, and sin | nilar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions th | at are shown as "typical", "average", "", etc.). |
| Ferminal Type And Quantity: | |
| 2 wire lead | |
| Specification Data: | |
| 96906-ms90537 government standard | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |

NSN 5950-00-932-2676

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

