

View Online at <https://aerobasegroup.com/nsn/5950-00-932-2817>

Reliability Indicator:

Established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.063 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.203 inches single group

Frequency Rating:

1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

2.750 inches

Body Height:

2.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

12.50 ac volts single component single secondary and 72.50 ac volts single component single secondary and 85.00 ac volts single component single secondary

Test Data Document:

13499-662-0194-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0