NSN 5950-00-932-2817

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-932-2817
Reliability Indicator:
Established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.063 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches single mounting facility single center group
Mounting Hole Diameter:
0.203 inches single group
Frequency Rating:
1.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.250 inches
Body Width:
2.750 inches
Body Height:
2.750 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
2.0 amperes ac single component single secondary
Winding Operating Voltage:
12.50 ac volts single component single secondary and 72.50 ac volts single component single secondary and 85.00 ac volts single
component single secondary
Test Data Document:
13499-662-0194-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
11 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0