

View Online at <https://aerobasegroup.com/nsn/5950-00-932-6794>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

284.4 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 4.870 inches and 5.000 inches

Body Width:

Between 4.120 inches and 4.250 inches

Body Height:

Between 4.620 inches and 4.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

2.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.50 ac volts single component 2nd secondary

Special Features:

One primary winding; seven secondary windings with the 2nd and 7th winding center tapped and the 6th winding multiple tapped w/o center tap

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

23 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0