

View Online at <https://aerobasegroup.com/nsn/5950-00-932-6870>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

9.000 inches

Body Width:

7.500 inches

Body Height:

5.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

400.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0