NSN 5950-00-933-4534

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-933-4534

| View Online at https://aerobasegroup.com/nsn/5950-00-933-4534 |
|--|
| Reliability Indicator: |
| Not established |
| Mounting Hole Diameter: |
| 0.182 inches single group and 0.192 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| Between 1.870 inches and 1.912 inches |
| Body Width: |
| 1.438 inches |
| Body Height: |
| 1.234 inches |
| Distance Between Mounting Facility Centers: |
| 1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Winding Operating Current: |
| 315.0 milliamperes ac single component single primary output |
| Winding Power Rating: |
| 15.75 volts-amperes single component single primary output |
| Winding Operating Voltage: |
| 6.80 ac volts single component single primary output and 15.00 ac volts single component single primary output and 26.00 ac volts single |
| component single primary output and 32.00 ac volts single component single primary output and 50.00 ac volts single component single |
| primary output |
| Terminal Type And Quantity: |
| 7 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

A058b0

Fiig: