

View Online at <https://aerobasegroup.com/nsn/5950-00-933-9195>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and salt spray resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.204 inches single group

Frequency Rating:

400.0 hertz single component and 800.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.188 inches

Body Outside Diameter:

2.000 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Winding Operating Current:

12.0 amperes ac single component single primary input

Winding Power Rating:

60.0 volts-amperes single component single primary output

Winding Operating Voltage:

115.00 ac volts single component single primary input

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0