NSN 5950-00-936-2682

Power Transformer - Page 1 of 1



| 0 |
|---|
| View Online at https://aerobasegroup.com/nsn/5950-00-936-2682 |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.234 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 3.500 inches |
| Body Width: |
| 3.000 inches |
| Body Height: |
| 3.310 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization: No

Fiig:

A058b0