NSN 5950-00-936-5031

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-936-5031

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Dust resistant and fungus resistant and humidity resistant and

Overall Length:

3.970 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.735 inches single mounting facility single center group and 1.765 inches single mounting facility single center group

Overall Height:

4.330 inches

Overall Width:

2.530 inches

Mounting Slot Width:

0.220 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Operating Temp:

160.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component

Winding Operating Current:

888.0 amperes ac single component single primary

Winding Operating Voltage:

208.00 ac volts single component single primary120.00 ac volts single component single primary or

Special Features:

Secondary rated but not included

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

NSN 5950-00-936-5031

Current Transformer - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A058b0