

View Online at <https://aerobasegroup.com/nsn/5950-00-936-5937>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.596 inches single mounting facility single center group and 0.604 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.596 inches single mounting facility single center group and 0.604 inches single mounting facility single center group

Frequency Rating:

3.0 kilohertz single component and 12.0 kilohertz single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.020 inches

Body Width:

1.020 inches

Body Height:

0.830 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

25.0 milliamperes dc single component single primary

Test Data Document:

03538-77c708612 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0