# NSN 5950-00-937-0422

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-937-0422

## Reliability Indicator:

Not established

## **Frequency Rating:**

400.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

## Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to terminal single component

### Body Length:

1.260 inches

Body Width:

1.175 inches

### Body Height:

1.000 inches

## Maximum Operating Temp:

125.0 degrees celsius

# Distance Between Mounting Facility Centers:

1.125 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

#### Mounting Facility Quantity:

2 single group

#### Mounting Method:

Threaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thread Size:

0.112 inches single group

#### Winding Operating Current:

1.0 microamperes ac single component single secondary and 3.0 milliamperes ac single component single secondary

#### Winding Operating Voltage:

10.00 ac millivolts single component single secondary and 30.00 ac volts single component single secondary

#### Thread Series Designator:

Unc single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5950-00-937-0422

Power Transformer - Page 2 of 2

**Fiig:** A058b0

