

View Online at <https://aerobasegroup.com/nsn/5950-00-937-8853>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.875 inches single mounting facility single center group

Frequency Rating:

388.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

8.657 inches

Body Width:

6.250 inches

Body Height:

5.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.3125 inches single group

Winding Operating Voltage:

254.00 ac volts single component single primary input

Test Data Document:

10001-2448399 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

3 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0