

View Online at <https://aerobasegroup.com/nsn/5950-00-940-8602>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group

Frequency Rating:

395.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 4.906 inches and 4.969 inches

Body Width:

Between 3.969 inches and 4.031 inches

Body Height:

3.375 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

67.45 ac volts single component 3rd secondary and 74.55 ac volts single component 3rd secondary

Special Features:

1 primary; 6 secondaries

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0