## NSN 5950-00-941-5966

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-941-5966

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

### **Overall Height:**

6.640 inches

### Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Transformer Winding Connection Type:**

Delta-wye

### **Maximum Transformer Power Rating:**

166.0 volt-ampere single component

### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

### **Body Length:**

4.690 inches

### **Body Width:**

4.000 inches

### **Body Height:**

6.000 inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### **Inclosure Type:**

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### **Thread Size:**

0.250 inches single group

### **Winding Operating Current:**

4.1 amperes ac single component single secondary

### **Winding Operating Voltage:**

23.50 ac volts single component single secondary

### **Thread Series Designator:**

Unc single group

# NSN 5950-00-941-5966

Power Transformer - Page 2 of 2



Terminal Type And	Quantity:
-------------------	-----------

6 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0