## NSN 5950-00-942-2681

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-942-2681

Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.375 inches
Body Width:
1.250 inches
Body Height:
1.375 inches
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
Mounting Method:
mounting metriou.
Unthreaded hole single group
•
Unthreaded hole single group
Unthreaded hole single group Winding Function And Quantity:
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary
Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 20.00 ac pounds per hour wet single component 2nd secondary Terminal Type And Quantity:
Unthreaded hole single group Winding Function And Quantity:  1 primary single component and 3 secondary single component Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary Terminal Type And Quantity:  8 wire lead
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary  Terminal Type And Quantity:  8 wire lead  Shelf Life:
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary  Terminal Type And Quantity:  8 wire lead  Shelf Life:  N/a
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary  Terminal Type And Quantity:  8 wire lead  Shelf Life:  N/a
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary  Terminal Type And Quantity:  8 wire lead  Shelf Life:  N/a  Unit Of Measure:
Unthreaded hole single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Winding Operating Voltage:  20.00 ac pounds per hour wet single component 2nd secondary  Terminal Type And Quantity:  8 wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: