

View Online at <https://aerobasegroup.com/nsn/5950-00-942-2726>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

6.000 inches

**Body Width:**

4.687 inches

**Body Height:**

4.000 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

20.0 amperes ac single component single secondary

**Winding Operating Voltage:**

4.00 ac volts single component single secondary

**Special Features:**

Primary has 1 tap by applying primary voltage to tap secondary voltage will be 7.5 v rms and 30.0 amps

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

3 solder stud and 2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0